

LUBRIPLATE® and FISKE® GREASE SHELF LIFE STATEMENT (years)												
PRODUCT	BIN	DRUM	QTR DRUM	PAIL	6 lb TUB	16 oz TUB	7 lb JUG	2 lb BOTTLE	CARTRIDGE	TUBE	AEROSOL CAN	BRICK
130 Series		5	5	5	5	5				10		
1444		5	5	5					5			
3H Direct				4					4	4	4	
730 Series		5	5	5					5			
777				3								
Bio-based EP-2 / ATB Biobased EP-2		3	3	3					5			
Bio-based Jack-Up Leg Grease				3								
Clearplex Series		3	3	3					3	10		
CS-FG/EP Series		5	5	5					5			
FGL Series		3	3	3	3	3			3		3	
Lithium/Lithplex Brick Grease												3
Pure Tac & Pure Tac Light		4	4	4					4			
SFL Series		4	4	4		4			4	10		
SYN ST High Performance H-1 Special				5					5			
SYNXTREME FG & HD Series		5	5	5					5		10	
SYNXTREME HT MAX				5					5			
SYNXTREME ASAP				3		3						
ALL OTHER GREASES	6	6	6	6	10	10	10	10	10	10	10	10

Listed above are typical shelf-life recommendations. Several factors, including storage conditions, can significantly alter the shelf life of the product.

LUBRIPLATE® and FISKE® brand products should be stored in a dry, covered (out of direct sunlight) environment between 40°F-120°F.

**For shelf life validation on a specific lot batch, contact:
LUBRIPLATE Lubricants Co., Technical Services @ 1-800-347-5343.**

LUBRIPLATE® and FISKE® OIL SHELF LIFE STATEMENT (years)												
PRODUCT	BIN	DRUM	QTR DRUM	PAIL	2½ gal JUG	7 lb JUG	1 gal JUG	2 lb BOTTLE	1 qt BOTTLE	PUMP SPRAY	AEROSOL CAN	TUBE
35 Soluble Oil		2	2	2			2					
377 Cutting Oil		5										
78 Oil-ZF	3	3		3								
981 & 989 Compr Oil		3		3								
Bio-Based Green Hyd. Fluid Series	3	3		3								
Biodegradable Penetrating Fluid		4	4	4			4				4	
Bio-SynXtreme Series		5	5	5								
Cut-N-Cool		2		2			2					
FMO-AW Series	5	5	5	5			5		5	5	5	10
Hydro Flush		10		10			10					
LowTemp Airline Lube						1						
Refrigeration Compr Oils 68-N & -P		2		2								
SCL-220, H1/220		5		5								
Seamer Oil FG-100,150	5	5										
SPIRAL FREEZER OIL		5										
Sugar Dissolving Oil		1		1			1			1	2	
SYN-FG SPRL FRZR CONVYR		5		5								
SYN HTF LIGHT	5	5		5								
SYNCOOL Series		5		5								
SYNXTREME AC SERIES		5		5								
SYNXTREME FRH1-46		5		5								
SYNXTREME HTCO MAX				1			1					
SYNXTREME HT MAX FLUSH								3				
UTF BIOBASED GREEN		1		1								
ZF AC-1 ORANGE		5		5								
ALL OTHER OILS	6	6	6	6	10	10	10	10	10	10	10	10

Listed above are typical shelf-life recommendations. Several factors, including storage conditions, can significantly alter the shelf life of the product. LUBRIPLATE® and FISKE® brand products should be stored in a dry, covered (out of direct sunlight) environment between 40°F-120°F.

**For shelf life validation on a specific lot batch, contact:
LUBRIPLATE Lubricants Co., Technical Services @ 1-800-347-5343.**